

TABLET METAL DETECTOR



Pharmaceutical Metal Detector

SPECIFICATIONS

VERSION	Digital Version
Aperture Size	75mm Width X 25mm Height
Types Of Metals Detected	All Type of Metals Are Detected. Fe, N Fe & Ss
Capacity	10000 Tablets Per Minute Max. For 12mm Dia Tablets 3000 To 5000 Tablets Per Minute Max For 25mm Dia Tablets
Supported Tablet Sizes	3mm Dia To 40mm Dia
Operating Voltage	160 - 230V, AC, 1PH, 50-60 Hz
Load	100VA
Total Weight	Approx. 60 Kgs
Rejection Mechanism	Flap Type High Speed Rotary Solenoid with Inbuilt Reject Collection Bin
Available Features	Data And Settings, Real Time Clock, Internal Memory Storages, 100 Product Memories, Parallel Printer & Also Through Rs 232, 3 Level Password Protection, Self Test Facility , 20ch X 4 Lines Lcd Display, 8 Keys Keypad Settings, Reject Confirmation, Rs 232 & 485
Infeed Height	675 mm To 1000 mm (adjustable)
Out Feed Height	425 mm TO 750 mm (adjustable)
Documentation	IQ, PQ, DQ, OQ validation protocol is provided
Certificates	Test Certificates, MOC, Warranty, Etc Included.

* Specification are subject to change without prior notice

Boghi Engineering & Software Technologies Pvt. Ltd.

Regd. Off: Plot No.11, Anandnagar-1, Bandlaguda, Nagole, Hyderabad-500068. Tel: 040-40245278.

Branch Off: 217, Maruthi Corporate Point, Swapnalok Complex, S.D. Road, Secunderabad-500003. Tel: +91-9347006933.

www.bestbig.net